



6 feet

C-View, Four Sided Fireplace Specifications

The C-view fireplace is an engineered system; please contact Montigo to confirm if your installation requirements are within the installation parameters of these standard specifications. This system is available with COOL PACK technology, which is optional for residential applications but required in public use applications. Also all C-View systems are power vented (see Power Vent specs for more details). C-View fireplaces are tested and certified to ANSI Standard C21.50 with CSA International US and Canada.

GLASS

- Viewing Area: See table below. Height 24" Standard.
 - Type: 5 mm thick Tempered glass.
 - Temperature
 - No COOL PACK: 210 deg. Fahrenheit
 - w/ COOL PACK: 160 deg. Fahrenheit
 - w/ Power COOL PACK: 110 deg. Fahrenheit
- } Temperatures in laboratory conditions.

AIR

- Consumption Setting: See table below. Required flow to actuate the controls system.
- Intake Size: As per factory shop drawings. For alternate options please contact Montigo.
- Intake Location: As per factory shop drawings. For alternate options please contact Montigo.

GAS

- Input: See table below.
- Control Valves: As per factory shop drawings. For alternate options please contact Montigo.
- Flue Gas Temperature: 340 deg. Fahrenheit.
- Propane Gas Burner: High Low Ribbon Burner Mix.
- Natural Gas Burner Options: High Low Burner, Ribbon Burner, or Concealed Burner available at request.

VENT

- Size: As per factory shop drawings. For alternate options please contact Montigo.

Glass Dimentions (2 per side)	BTUs	No Cool Pack CFM	Cool Pack CFM	Power Cool Pack CFM
72" x 72"	320,000	1,600	2,080	2,560
72" x 84"	360,000	1,800	2,320	2,840
72" x 96"	400,000	2,000	2,560	3,120
72" x 108"	440,000	2,200	2,800	3,400
72" x 120"	480,000	2,400	3,040	3,680